

PA-UL-LN55E.R001



*picture only for reference

Dimensions

Length	67	± 1mm
Width	22.5	± 0.5mm
Height	72	± 1mm



MH45979



IEC 62133 2nd. Ed.

Data for Pack

Nominal voltage		3.6V	2.5V - 4.2V
Nominal capacity		11.6Ah	typical
Used cell in pack		4pcs	Panasonic NCR-18650
Internal resistance pack		60mΩ	±10%
Charge voltage		4.2V	max
Charge current	standard	1.65A	0°C < T < 45°C
	rapid	3A	10°C < T < 45°C (limited by connector)
Discharge	standard	1.65A	-20°C < T < 60°C ^{*1)}
	max cont.	3A	-20°C < T < 60°C ^{*1)} (limited by connector)
	max peak	10A	-20°C < T < 45°C t < 2ms ^{*1)}
Short circuit current		≤ 53.6	< 380μs
NTC		10kΩ	Tolerance ±3%; B-value 25°C/85°C = 3980K
Connector	JST	XHP-3	Pin1 GND
			Pin2 NTC
			Pin3 Bat+
Cable Length		45mm	± 5mm
Weight		ca. 174g	± 5g
Watt-hour rating		39.2Wh	acc. to UN38.3 Certificate

*1) discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4215mV	±25mV
	release	4100mV	±25mV
under voltage (per cell)	cut off	2300mV	±50mV
	release	2400mV	±50mV
Current Limit 1 by SU		≤ 4A	continous typical
Current Limit 2 by SU		≥17.9A	2.24ms (typical)
short circuit protection		≥42.9A	380μs (typical) ±10A
Power consumption	active	15μA	±5μA
	power down	8μA	±2μA

Recommended Charger

C-LIO-1SN15-1,8M-DIN4-GPN-.R001