

# PA-UL-LNB46.R001



\*picture only for reference

## Dimensions

Length	67	± 1mm
Width	18.6	± 0.5mm
Height	41	± 1mm



MH45979



IEC 62133 2nd. Ed.

## Data for Pack

Nominal voltage	3.6V	2.5V - 4.2V		
Nominal capacity	6700mAh	typical		
Used cell in pack	2pcs	Panasonic NCR-18650BF		
Internal resistance pack	100mΩ	±10%		
Charge voltage	4.2V	max		
Charge current	standard	1.1A	10°C < T < 45°C	
	rapid	2.4A	10 °C < T < 45°C (limited by cell)	
Discharge	standard	1.1A	-20°C < T < 60°C *1)	
	max cont.	3A	-20°C < T < 60°C *1) (limited by connector)	
	max peak	10A	-20°C < T < 45°C t < 2ms *1)	
Short circuit current	≤ 63A	< 380μs		
NTC	10kΩ	Tolerance ±3%; B-value 25°C/85°C = 3980K		
Connector	JST	XHP-3	Pin1	GND
			Pin2	NTC
			Pin3	Bat+
Cable Length	45mm	± 5mm		
Weight	ca. 90g	± 5g		
Watt-hour rating	24Wh	acc. to UN38.3 Certificate		

\*1) discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

## Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4215mV	±25mV
	release	4100mV	±25mV
under voltage (per cell)	cut off	2300mV	±50mV
	release	2400mV	±50mV
Current Limit 1 by SU		≤ 4A	continous typical
Current Limit 2 by SU		≥17.9A	2.24ms (typical)
short circuit protection		≥42.9A	380μs (typical) ±10A
Power consumption	active	15μA	±5μA
	power down	8μA	±2μA

## Recommended Charger

C-LIO-1SN15-1,8M-DIN4-GPN-.R001

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

Fey Elektronik GmbH, Storchenweg 3, 21217 Seevetal, Germany | info@feyelektronik.de, Tel.: +49 (0)40-703-8888-0 Date: 26.04.2021